

## Wildcard T400P

The Wildcard T400P offers unprecedented density and value in the telephony arena. Terminating four T1/PRI interfaces in a single PCI form-factor device, the T400P harnesses the benefits of standard PC hardware and the Open Source Linux operating system.


Digium T1 interfaces interconnecting a Linux PC system with traditional telephony equipment enable the flexibility of Open telephony solutions. In addition to conventional telephony, the Open Source Asterisk PBX (Private Branch Exchange) software extends the strengths of the T400P to provide Voice over IP (VoIP) bridging ultra low-latency TDM over Ethernet (TDMoE) for greater efficiency and flexibility.

The T400P supports industry standard telephony and data protocols, including Robbed Bit Signalling (RBS) and Primary Rate ISDN (PRI) protocol families for voice, as well as PPP, Cisco HDLC, and Frame Relay data modes. The board is fully supported by the Asterisk Open Source PBX and can drive both line-side and trunk-side interfaces, and includes support for advanced call features.

If you would like information concerning our European equivalent of the T400P, the E400P, please see the T400P product data sheet available at <http://www.digium.com/>.

### Target Applications

- Packet Voice Gateways and Switches
- Calling Card Services
- One Number Services
- Message Services
- Conferencing
- Customized and Web Telephony
- Voice/Data Intergration
- Future-Proof PBX
- ISDN Remote Access Servers



### PRI Switch Capatibility

- AT&T 4ESS
- DMS 100
- Lucent 5E
- National ISDN 2
- Network or CPE

### RBS Voice Modes

- A-Law, Mu-Law, and Linear Modes Supported
- E&M
- E&M Wink
- Feature Group D
- Groundstart (FXO and FXS)
- Loopstart (FXO and FXS) with Optional Disconnect Supervision

T400P - Ultimate Density and Performance in T1

digium\*

### Data Modes

SyncPPP (both Fixed and Dialup)  
Frame Relay  
Cisco HDLC

### Services and Features

CallerID  
Transmission/Reception Pseudo-TDM Conferencing with Zaptel Channels  
Digital Gain Control (Transmit and Receive)  
Dynamic Span Interaction (TDM over Ethernet)  
Echo Cancellor  
ISDN RAS Capability  
Local and Remote Loop Backs  
Pseudo-TDM Bus Architecture Keeps Latency Low  
Supports Same Span Voice and Data  
Tone Internationalization (Tone Zones)

### Environment Conditions

Operation Range: 0 to 50° C, 32 to 122° F  
Storage Range: -20° to 65 C, 4 to 149° F  
Humidity: 10-90% non-condensing

### Hardware and Software Requirements

800 Mhz Pentium III or better with 64MB RAM  
Available PCI Slot  
Linux 2.4 Kernel

Combined with Digium's Asterisk Open Source PBX, the T400 provides a platform for deploying customizable, high-density voice and data services over a variety of network configurations and applications at a market-leading cost.

### Contact Information

1-877-LINUX-ME  
[sales@digium.com](mailto:sales@digium.com)  
<http://www.digium.com/>

digium

T400P - Ultimate Density and Performance in T1

digium